


FILTOWER F-100

(667.100)

Voltage	(V)	400	Filter surface	(m ²)	100
Motor	(kW)	2 x 3,0	No. of filter elements	(pc)	4
Ampere	(A)	8,5	Filter material		Dust class M
Rated frequency	(Hz)	50	Filter cleaning		Jet-cleaning
Fuse	(A)	C16	Weight	(kg)	ca. 1.100
Intake port (L x W)	(mm)	1.295 x 295	Collection bin	(liter)	ca. 100-150
max. neg. pressure intake	(Pa)	2.800	Dimensions (L x W x H)	(mm)	2.060 x 1.515 x 2.910
max. air flow	(m ³ /h)	10.000	Compressed air requirement	(l/Impuls)	70 at 0,120s
Sound level	(dBA)	68	Compressed air connection	(inch)	¼"



ESTA PLUS

Application range:

- Fume extraction of dry, oil-free welding fumes arising during welding of metals
- For improving room air quality

Your benefits at a glance:

- Efficient welding fume exhaust using thermal lift from the welding process
- Ready to use – the filter tower comes preassembled
- Low operating costs thanks to cleanable permanent filter cartridges
- Compact design with low space requirements
- Flexibility – can be moved any time to a different set-up location

Characteristics:

- Jet filter cleaning
- Cleanable permanent filter cartridge featuring dust class M
- Newly conceptualised EasyControl controller
- Integrated spark protection

Options:

- Activation via potential-free contact
- Active charcoal inserts in front of outlet openings
- Model featuring frequency inverter, **eco+**, **ecotemp**, **4.0**
- **ecotemp** with heat exchanger
- Available in a W3-tested version for exhausting welding fumes from high-alloy steel

State of the art: 667100-51-02 Subject to change without notice! For remaining questions, please do not hesitate to contact us.

ESTA Apparatebau GmbH & Co. KG
 Gotenstraße 2 – 6
 89250 Senden

Telefon 07307804-0
 Telefax 07307804-500
 E-Mail info@esta.com

www.esta.com